

Mini Component System



NX-D2 Key Features

A powerful 230-watt mini system with three-way speakers, "dual design" for iPod, Vario Bass, USB Host, CD player, and AM/FM tuner. It also features motion sensor wake-up from standby mode, and touch panel design. The included remote features dedicated iPod control keys that simulate the iPod control wheel layout. Users can easily shuffle, repeat, scroll and select songs from the iPod menu.

Product Highlights

- :: "Dual Design" for iPod
- :: Video Output for iPod
- :: Touch Panel and Motion Sensor
- :: Subwoofer Level Control
- :: Mic Inputs(2) with Digital Echo
- :: Vario Bass
- :: Plays MP3/WMA with ID3/WMA Tags.
- :: 230 Watts Total Power
- :: Digital Tuner
- :: 3-way Speaker Design
- :: Clock/3-Preset Timer
- :: USB Host
- :: Remote Control

Details, Weights & Measures

CENTER UNIT

Dimensions (WxHxD) in.: $7 \frac{11}{16} \times 13 \frac{1}{8} \times 12 \frac{3}{8}$

Weight: 7.9 lbs

SPEAKERS

Dimensions (WxHxD) in.: $8 \frac{1}{8} \times 16 \frac{3}{16} \times 11 \frac{1}{2}$

Weight: 7.9 lbs

Specifications are subject to change without notice.

Specifications

AMPLIFIER/TUNER		CONNECTION FOR IPOD	
Power Output (with 0.7% THD)	230W	Control Keys	Play, Pause, Skip, Fast Forward/Rewind, Repeat, Shuffle, Menu, Select, Up/Down Arrow
Vario Bass (TURBO/ MOVIE/ LITeEASY/ AUTO)		Support Device	4G or Later
Live Surround (DANCE/HALL/STADIUM)		Video Out	
Sound Mode (ROCK/POP/CLASSIC)		Power Supply	
Manual Equalizer	(3-Mode)	USB HOST	
Subwoofer Level Control		Playable Formats	MP3, WMA (with ID3/WMA Tag)
MIC Input with MIC Level Control		GENERAL	
Digital Echo		Touch Panel	
Audio Input	(Front Stereo Mini Jack)	Motion Sensor	
Tuner Preset Stations	15 AM, 30 FM	Programmable Timer (Daily/Sleep)	
CD PLAYER		COMPU PLAY	
Playable Formats		Rotary Encoder Volume Control	Touch Panel
CD/CD-R/RW		Demo Mode	
MP3 (CD-R/RW)	(CD-R/RW, USB), with ID3 Tag	Remote Control	
WMA	(CD-R/RW, USB), with WMA Tag	SPEAKERS	
Mechanism Type	1-CD Tray	Magnetically Shielded	
Output Signal Level		Type	3-Way, Linear Phase Construction Speakers
Composite	1.0Vp-p/75 ohms	Woofer	6-5/16" (16cm), Cone
Dynamic Range	80dB	Midrange	2" (5cm), Cone
Signal-to-Noise Ratio	80dB	Tweeter	13/16" (2cm), Dome
Total Harmonic Distortion	0.01%	Power Handling Capacity	115W x 2
Audio Decoder		Impedance	3 ohms
MPEG Multichannel	(2.1ch)		
192kHz/24-bit Audio D/A Converter			
Number of Programs	32		
Repeat Play	(1 Track/ All Tracks/ Group)		
Smart Random Play			
Tray-Lock Function			
TERMINALS			
Digital			
Analogue			
Composite			
Headphone Out			
USB Host* [1]			

Specifications are subject to change without notice.

DISTRIBUTED BY

JVC U.S.A.

A Division of JVC Americas Corp.

1700 Valley Road, Wayne, NJ 07470

www.jvc.com

"JVC" is the trademark of Victor Company of Japan, Limited.