

Super Slim Soundbar Home Theater System, TH-BS7



TH-BS7 Key Features

The TH-BS7 Soundbar system is designed to match the slimmest of flat panel HDTVs. It includes a super slim soundbar that measures just 1.4 inches (36mm) tall, an even slimmer wall-mountable amplifier/control unit and a wireless subwoofer.

Specifications

- :: 180W Total Power
- :: Dolby Digital/DTS Decoders
- :: Ultra-Slim Design
- :: Wall-Mountable Pole-Type Speaker
- :: Vertical/Horizontal Layout Free Amplifier
- :: Original Direct Drive (DD) Speaker x 4
- :: Original 4.1-ch Front Surround System
- :: Dolby Digital/DTS Decoders
- :: Optical Digital Input x 3
- :: Remote Control
- :: Wireless 6-5/16" (16cm) Powered Subwoofer

Details, Weights & Measures

CENTER SPEAKER

Dimensions (WxHxD) in.: $35 \frac{7}{8} \times 1 \frac{1}{2} \times 2 \frac{1}{8}$

Weight: 3.5 lbs

AMPLIFIER

Dimensions (WxHxD) in.: $7 \frac{3}{8} \times 1 \frac{1}{4} \times 11 \frac{13}{16}$

Weight: 1.6 lbs

SUBWOOFER

Dimensions (WxHxD) in.: $8 \frac{1}{2} \times 13 \frac{7}{8} \times 10$

Weight: 11 lbs

Specifications are subject to change without notice.

Specifications

POWER OUTPUT	
Power Output (with 10% THD)	20 watts per channel, min.RMS, driven into 4 ohms, at 1kHz, with no more than 10% total harmonic distortion (Amp)
Total	180 watts
Front	1-Way, 4-Speaker, Acoustic Suspension
Center	20W/4 ohms per speaker
Surround	20W/4 ohms per speaker
Subwoofer	100 Watts
CENTER UNIT	
Power Output	
Display Dimmer	Yes (3-Step)
TERMINALS	
Analog (RCA) Audio In/Out	Yes (x 1) / -
Digital (Optical) Audio In/Out	Yes (x 3) / -
DECODER/CIRCUITRY	
Dolby Digital Decoder	Yes
DTS Decoder	Yes
Front Surround	Yes
PCM Decoder	Yes (on Remote)
AMPLIFIER	
Power Consumption	
Power On	30W
Standby	Less than 1W
Remote Control Unit	Yes
Fade Muting	Yes
SUBWOOFER	
Type	6-5/16" (16cm) Cone, Bass-Reflex
Powered	Yes
Power Handling Capacity/Impedance	100W/3 ohms
Frequency Range	45Hz - 5kHz
Sound Pressure Level	82dB/W.m
Power Requirements	AC 120V, 60Hz
Power Consumption	
Power On	30W
Standby	Less than 1W
FRONT / CENTER / SURROUND SPEAKERS	
Front Speaker (Magnetically Shielded)	20 watts per channel, min.RMS, driven into 4 ohms, at 1kHz, with no more than 10% total harmonic distortion (Amp)

Specifications are subject to change without notice.

DISTRIBUTED BY



JVC U.S.A.
 A Division of JVC Americas Corp.
 1700 Valley Road, Wayne, NJ 07470
www.jvc.com

"JVC" is the trademark of Victor Company of Japan, Limited.