

## Dual Wireless Soundbar Home Theater System, TH-BA3



### TH-BA3 Key Features

World's first dual wireless soundbar system that features a wireless subwoofer and wireless surround speakers.

### Specifications

- :: Wall-Mountable Soundbar with 3-3/16 (8cm) Full-Range Speaker Units (x4)
- :: Wireless 6-5/16" (16cm) Powered Subwoofer
- :: 280W Total Power
- :: Dolby Digital/Dolby Pro Logic II/DTS Decoders
- :: 5.1-ch Surround Sound System
- :: Vertical/Horizontal Layout Free Amplifier for Surround Speakers
- :: Optical Digital Input x 2
- :: Remote Control

### Details, Weights & Measures

CENTER UNIT	
Dimensions (WxHxD) in.:	35 <sup>7</sup> / <sub>16</sub> x 4 <sup>15</sup> / <sub>16</sub> x 3 <sup>3</sup> / <sub>8</sub>
Weight:	7.8 lbs
FRONT/CENTER/SURROUND SPEAKERS	
Dimensions (WxHxD) in.:	4 <sup>3</sup> / <sub>16</sub> x 4 <sup>11</sup> / <sub>16</sub> x 3 <sup>7</sup> / <sub>8</sub>
Weight:	1.1 lbs
SUBWOOFER	
Dimensions (WxHxD) in.:	8 <sup>1</sup> / <sub>2</sub> x 13 <sup>7</sup> / <sub>8</sub> x 10
Weight:	11.1 lbs

Specifications are subject to change without notice.

# Specifications

POWER OUTPUT	
Power Output (with 10% THD)	30 watts per channel, min. RMS, driven into 4 ohms, at 1kHz, with no more than 10% total harmonic distortion (Speaker)
Total	280 watts
Front	30W/4 ohms per speaker
Center	30W/4 ohms per speaker
Surround	30W/4 ohms per speaker
Subwoofer	100 Watts
CENTER UNIT	
Power Output	
Rear	30W/4 ohms per speaker
Display Dimmer	Yes (3-Step)
TERMINALS	
Analog (RCA) Audio In/Out	Yes (x 1) / -
Digital (Optical) Audio In/Out	Yes (x 3) / -
DECODER/CIRCUITRY	
Dolby Digital Decoder	Yes
DTS Decoder	Yes
Dolby Pro Logic II Decoder	Yes
PCM Decoder	Yes (on Remote)
AMPLIFIER	
Power Consumption	
Power On	30W
Standby	Less than 1W
Remote Control Unit	Yes
Fade Muting	Yes
SUBWOOFER	
Type	6-5/16" (16cm) Cone, Bass-Reflex
Powered	Yes
Power Handling Capacity/Impedance	100W/3 ohms
Frequency Range	45Hz - 5kHz
Sound Pressure Level	82dB/W.m
Power Requirements	AC 120V, 60Hz
Power Consumption	
Power On	30W
Standby	0.95W
FRONT / CENTER / SURROUND SPEAKERS	
Surround Speakers (Magnetically Shielded)	1-Way, Bass-Reflex
Configuration	3-3/16" (8cm), Full-Range x 4
Wall-Mountable	Yes
Power Handling Capacity/Impedance	30W/4 ohms
Frequency Range	84Hz - 22kHz
Sound Pressure Level	82dB/W.m

Specifications are subject to change without notice.

DISTRIBUTED BY



**JVC U.S.A.**  
 A Division of JVC Americas Corp.  
 1700 Valley Road, Wayne, NJ 07470  
[www.jvc.com](http://www.jvc.com)

"JVC" is the trademark of Victor Company of Japan, Limited.