



Report ID: MRI9AIKG5007727U3a

# **MSDS**

& Model

Applicant

Cosonic Intelligent Technologies Co., Ltd.

NO.3 Keyuan Road, Songshan Lake District, Dongguan City, Address

**Guangdong Province** 





No.: MRI9AIKG5007727U3a

Code: 4zt3q7t



- 1. 本报告无检验检测专用章、报告骑缝章和批准人签章无效。
  - This report is invalid without special seal for inspection and test, cross-page seal and signature of the approver.
- 2. 本报告页面所使用 "PONY"、"谱尼"字样为本单位的注册商标, 其受《中华人民共和国商标法》保护, 任何未经本单位授权的擅自使 用和仿冒、伪造、变造"PONY"、"谱尼"商标均为违法侵权行为,本单位将依法追究其法律责任。

The words "PONY" and "i情光" used in this report page are the registered trademarks of the company, which are protected by the Trademark Law of the People's Republic of China. Any unauthorized use, counterfeiting, forging or altering of the trademarks of "PONY" and "请光" without the authorization of the company is an illegal infringement, and the company will investigate their legal liabilities according to law.

- 3. 委托单位对报告数据如有异议、请于报告完成之日起十五日内向本单位书面提出复测申请,同时附上报告原件并预付复测费。 If the applicant has any objection to the report data, please submit a written application for retesting to PONY within 15 days after the completion of the report, with the original report attached and the retesting fee prepaid.
- 4. 不可重复性或不能进行复测的实验,不进行复测,委托单位放弃异议权利。 If the experiment cannot be repeated or cannot be retested, no retest shall be conducted, and the appliant shall waive the right of objection.
- 5. 委托单位必须保证送至本公司的样品及资料与真实的出运货物相一致、如有不符、所涉及的法律责任及其他后果均由委托单位自行承担。 The client must guarantee that samples and documents provided for appraisal are consistent with the goods to be transported. Otherwise, the client shall bear all legal responsibilities and other consequences due to it.
- 6. 本报告仅对所测样品的检测结果负责,检测结果及其相关判定结论仅反映对所测样品的评价或只代表检测时污染物的排放状况。对于报 告及所载内容不能进行商业广告宣传使用,使用所产生的直接或间接损失及一切法律后果,本单位不承担任何经济和法律责任。

This report is only responsible for the test results of the tested samples. The test results and relevant conclusions reflect the evaluation of the tested samples or only represent the emission status of pollutants during the test. The report and the contents contained in it cannot be used for commercial advertising, and PONY does not assume any economic and legal liabilities for direct or indirect losses and all legal consequences arising from the use.

- 7. 本单位有权在完成报告后按规定方式处理所测样品,除客户特别声明并支付样品管理费,所有超过标准规定时效期的样品均不再做留样。 PONY has the right to dispose the tested sample after approval of the test report. Unless the applicant specifically declares and pays the sample management fee, all samples beyond the validity period specified in the standard will not be retained.
- 8. 本单位保证工作的客观公正性, 对委托单位的商业信息、技术文件等商业秘密履行保密义务。 PONY assures objectivity and impartiality of the test, and fulfills the obligation of confidentiality for applicant's commercial information, and technique document.
- 9. 本报告私自转让、盗用、冒用、涂改、未经本单位批准的复制(全文复制除外)或以其它任何形式的篡改均属无效,本单位将对上述行为 严究其相应的法律责任。

Any unauthorized transfer, appropriation, falsification, alteration, copying (except full text copying) or alteration in any other form of this report without the approval of PONY shall be invalid. PONY shall strictly investigate the corresponding legal liability for the aforesaid behavior.

10. 本报告不考虑国家及经营人差异。

The certificate/report takes no account of the differences of countries and applicants.

#### ▲ 防伪说明:


1.报告编号是唯一的;

The report number is unique.

2.扫描报告首页下方二维码或登录网站(http://www.ponytest.com/),即可查询报告真伪。

Scan the QR code below the first page or Log on to the website(http://www.ponytest.com/)to check the authenticity of the report.

哈尔滨实验室: (0451) 58627755 成都实验室: (028) 87702708 杭州实验室: (0571) 87219096







北京实验室:(010)83055000 郑州实验室:(0371)69350670 成都港尼计量实验室(028)87702708 宁波实验室:(0574)87736499 北京谱尼科技公司: (010) 80415661 郑州蒂尼职业卫生公司: (0371) 80967099 贵州实验室: (0851) 85221000 合肥实验室: (0551) 63843474 北京谱尼计量实验室:(010)82492998 新疆实验室:(0991)6684186 上海实验室:(021)64851999 深圳实验室:(0755)26050909 青岛实验室: (0532)88706866 石家庄实验室: (0311)85376660 苏州实验室: (0512)62997900 深峭配洲野途 (0755)26050909-846 天津实验室:(022)23607888 西安实验室:(029)89608785 苏州汽车座椅实验室及几童安全座椅 谱尼深圳通测:(0755)27673339 长春实验室: (0431)80530198 西安地信息科技有限公司: (029)81123093 碰撞实验室: (0512)62997900 广州实验室: (020)89224310 沈阳实验室: (024) 22811886 西安查德威柱副技术公司: (029) 85729073 武汉实验室: (027) 83997127 南宁实验室: (0771) 5518818

大连实验室:(0411)87336618 呼和浩特实验室:(0471)3450025 武汉车附所:(027)82318175 厦门实验室:(0592)5568048



Report No.: MRI9AIKG5007727U3a Date: 2024-01-08 Page 1 of 10

# **Material Safety Data Sheet**

Reference to ST/SG/AC.10/30/Rev.10 (GHS)

# Section 1 - Chemical Product and Company Identification

**Chemical Product Identification** 

Sample Name: Rechargeable Li-ion Battery

Sample Model: 401029 Recommended Uses: N/A Restrictions on Use: N/A

Supplier Name: Chongqing VDL Electronics Co., Ltd.

Address: Building1-4, Puli Industrial New Area, Zhaojia Street, Kaizhou District, Chongqing, China.

Phone Number: +86-755-29961201(8036)

FAX: 023-5297-5969

E-mail: PUR03@gdvdl.com

Emergency Phone Number: 023-5297-7888

## Section 2 - Hazards Identification

Emergency overview: This product is a battery. Intended use of the product should not result in exposure to the chemical substance. In case of rupture the below hazards exist.

#### Classification according to GHS

Acute toxicity, oral (4)

Skin corrosion/irritation (2)

Serious eye damage/eye irritation (2A)

Specific target organ toxicity, single exposure; Respiratory tract irritation (3)

#### Label elements

Hazard pictogram(s):



Signal word:

Warning

Hazard statement(s):

H302 Harmful if swallowed

H315 Causes skin irritation

H319 Causes serious eye irritation

H335 May cause respiratory irritation

Precautionary statement(s):

( Hotline 400-819-5688 Pony Testing Group Shenzhen Co., Ltd. www.ponytest.com

Address: 3/F. of Building 2, Building 1, Xinhaosheng Industrial Park, Yonghe Road, Qiaotou Community, Baoan District, Shenzhen, Guangdong, China Testing Address: 3/F. of Building 2, Building 1, Xinhaosheng Industrial Park, Yonghe Road, Qiaotou Community, Baoan District, Shenzhen, Guangdong, China Tel: 0755-26050909 Fax: 0755-26068336



Report No.: MRI9AIKG5007727U3a Date: 2024-01-08 Page 2 of 10

#### Prevention:

P264 Wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves, protective clothing, eye protection, face protection.

P261 Avoid breathing dust, fume, gas, mist, vapours, spray.

P271 Use only outdoors or in a well-ventilated area.

#### Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTER if you feel unwell.

P330 Rinse mouth.

P302 + P352 IF ON SKIN: Wash with plenty water.

P321 Specific treatment (See additional emergency instructions).

P333 + P313 If skin irritation or rash occurs: Get medical advice.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER, if you feel unwell.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

#### Disposal:

P501 Send contents to approved waste treatment plants.

#### Other hazards

Physical and chemical hazards: See Section 10

Human health hazards: See Section 11 Environmental hazards: See Section 12

# Section 3 – Composition/Information on Ingredients

Chemical characterization: Mixture

Chemical Composition	CAS No.	EC#	Weight (%)
Cobaltate, lithium	12190-79-3	235-362-0	30-50
Carbon black	1333-86-4	215-609-9	0.5-1
Polyvinylidene fluoride resin	24937-79-9	607-458-6	0.5-1
Aluminium	7429-90-5	231-072-3	5-10

(C) Hotline 400-819-5688 Pony Testing Group Shenzhen Co., Ltd.

Tel: 0755-26050909



Report No.: MRI9AIKG5007727U3a Date: 2024-01-08 Page 3 of 10

Graphite	7782-42-5	231-955-3	15-25
Styrene-butadiene rubber 1500	9003-55-8	618-370-2	0.2-1
Sodium carboxy methyl cellulose	9004-32-4	618-378-6	0.2-1
Copper	7440-50-8	231-159-6	5-15
Nickel	7440-02-0	231-111-4	0.5-1.5
Phosphate(1-), hexafluoro-, lithium	21324-40-3	244-334-7	15-25
Polyethylene	9002-88-4	618-339-3	1-5
Nylon	24937-16-4	607-456-5	0.5-1
Polypropylene	9003-07-0	618-352-4	1-2

#### Section 4 - First Aid Measures

#### Description of first aid measures

General information No special measures required.

#### After eye contact

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

#### After skin contact

Remove contaminated clothing and shoes. Immediately wash with water and soap and rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.

#### After inhalation

Remove victim to fresh area. Administer artificial respiration if breathing is difficult. Seek medical attention.

#### After swallowing

Do not induce vomiting. Get medical attention.

Personal protective equipment for first-aid responders: No data available.

Most important symptoms/effects, acute and delayed: No data available.

Indication of immediate medical attention and special treatment needed: Treat symptomatically.

# Section 5 - Fire Fighting Measures

#### Suitable extinguishing media:

Small Fire: Dry chemical, CO2, water spray or regular foam. Large Fire: Water spray, fog or regular foam. Move containers from fire area if you can do it without risk.

#### Unsuitable extinguishing media:

No data available.

( Hotline 400-819-5688 Pony Testing Group Shenzhen Co., Ltd. www.ponytest.com

Address: 3/F. of Building 2, Building 1, Xinhaosheng Industrial Park, Yonghe Road, Qiaotou Community, Baoan District, Shenzhen, Guangdong, China Testing Address: 3/F. of Building 2, Building 1, Xinhaosheng Industrial Park, Yonghe Road, Qiaotou Community, Baoan District, Shenzhen, Guangdong, China Tel: 0755-26050909 Fax: 0755-26068336



Report No.: MRI9AIKG5007727U3a Date: 2024-01-08 Page 4 of 10

#### Specific Hazards arising from the chemical:

Special hazards arising from the substance or mixture

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature(>150°C(302°F)), when damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in close proximity.

#### Specific protective actions for fire-fighters:

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

#### Section 6 - Accidental Release Measures

#### Personal precautions:

As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions. Keep unauthorized personnel away. Stay upwind, uphill and/or upstream. Ventilate closed spaces before entering. Large Spill: Consider initial downwind evacuation for at least 100 meters (330 feet).

#### Protective equipment:

No data available.

#### **Emergency procedures:**

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Absorb with earth, sand or other non-combustible material. Leaking batteries and contaminated absorbent material should be placed in metal containers.

#### Environmental precautions:

Do not allow material to be released to the environment without proper governmental permits.

#### Methods and materials for containment and cleaning up:

For all waste handing must refer to United Nations, National and Local Regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# Section 7 - Handling and Storage

#### Precautions for safe handling:

Avoid short circuiting the battery. Avoid mechanical damage of the battery. Do not open or disassemble. Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area.



Report No.: MRI9AIKG5007727U3a Date: 2024-01-08 Page 5 of 10

Prevent concentration in hollows and sumps.

#### Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well-ventilated place. Keep away from heat, avoiding the long time of sunlight.

# Section 8 - Exposure Controls/Personal Protection

#### Control parameters

CAS No.	ACGIH	NIOSH	OSHA
12190-79-3	N/A	N/A	N/A
1333-86-4	TLV-TWA 3mg/m <sup>3</sup>	REL-TWA 3.5mg/m <sup>3</sup>	PEL-TWA 3.5mg/m <sup>3</sup>
24937-79-9	N/A	N/A	N/A
7429-90-5	29-90-5 TLV-TWA 1mg/m <sup>3</sup> REL-TWA 5mg REL-TWA 10mg		PEL-TWA 5mg/m <sup>3</sup> PEL-TWA 15mg/m <sup>3</sup>
7782-42-5	TLV-TWA 2mg/m <sup>3</sup>	REL-TWA 2.5mg/m <sup>3</sup>	PEL-TWA 15mppcf PEL-TWA 20mppcf
9003-55-8	N/A	N/A	N/A
9004-32-4	N/A	N/A	N/A
7440-50-8		REL-TWA 1mg/m <sup>3</sup> REL-TWA 0.1mg/m <sup>3</sup>	PEL-TWA 0.1mg/m <sup>3</sup> PEL-TWA 1mg/m <sup>3</sup>
7440-02-0	TLV-TWA 1.5mg/m <sup>3</sup>	REL-TWA 0.015mg/m <sup>3</sup>	PEL-TWA 1mg/m <sup>3</sup>
21324-40-3	N/A	N/A	N/A
9002-88-4	N/A	N/A	N/A
24937-16-4	N/A	N/A	N/A
9003-07-0	N/A	N/A	N/A

#### Appropriate engineering controls:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.


Wash hands before breaks and at the end of work.

#### Personal Protective Equipment:

Respiratory protection: Wear suitable protective mask. For a large large number of battery leakages, wear chemical protective clothing, including self-contained breathing apparatus.

Hand Protection: Wear appropriate protective gloves to reduce skin contact.

Eye Protection: Wear safety goggles or eye protection combined with respiratory protection.





Report No.: MRI9AIKG5007727U3a Date: 2024-01-08 Page 6 of 10

Skin and Body Protection: Working environment required, wear suitable protective clothing to minimize contact with skin. The type of protective equipment must be according to the concentration and the content of certain hazardous substances in the workplace.

# Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Colour: Silver.

Prismatic. Physical State:

Odour: Not available. pH: Not available.

Not available. Melting point/freezing point:

Boiling point or initial boiling point and boiling range: Not available.

Flash Point: Not available. Not available.

Flammability: Not available. Solubility:

Lower and upper explosion limit/flammability limit: Not available.

Auto-ignition temperature: Not available.

Decomposition temperature: Not available.

Not available. Kinematic viscosity: Partition coefficient: n-octanol/water (log value): Not available.

Vapour pressure: Not available.

Density and/or relative density: Not available.

Not available. Relative vapour density:

Particle characteristics: Not available.

Other information:

Voltage 3.7V Electric capacity 90mAh 0.333Wh Electric Energy

# Section 10 - Stability and Reactivity

Yonghe Road, Qiaotou Community, Baoan District, Shenzhen, Guangdong, China

Reactivity: No data available. Chemical stability: Stable.

Possibility of hazardous reactions: No data available.

Conditions to Avoid: Flames, sparks, and other sources of ignition, incompatible materials.

Incompatible materials: Oxidizing agents, acid base.

( Hotline 400-819-5688 Pony Testing Group Shenzhen Co., Ltd.



Report No.: MRI9AIKG5007727U3a Date: 2024-01-08 Page 7 of 10

Hazardous decomposition products: Carbon monoxide, carbon dioxide, lithium oxide fumes.

# Section 11 - Toxicological Information

#### Acute Toxicity:

CAS No.	LC50/LD50		
12190-79-3	No data available.		
1333-86-4	No data available.		
24937-79-9	No data available.		
7429-90-5	No data available.		
7782-42-5	No data available.		
9003-55-8	No data available.		
9004-32-4	No data available.		
7440-50-8	No data available.		
7440-02-0	LD50 Rat (oral): >9000mg/kg		
21324-40-3	No data available.		
9002-88-4	No data available.		
24937-16-4	No data available.		
9003-07-0	No data available.		

Skin corrosion/irritation: No data available.

Serious eye damage/irritation: No data available. Respiratory or Skin sensitization: No data available.

Germ Cell mutagenicity: No data available.

Carcinogenicity: No data available.

Reproductive toxicity: No data available.

Specific target organ toxicity-Single exposure: No data available. Specific target organ toxicity-Repeated exposure: No data available.

Aspiration hazard: No data available.

Information on the likely routes of exposure: No data available.

Eye: No data available. Skin: No data available. Ingestion: No data available. Inhalation: No data available.

PONY-BGLS186-03E-027-2023B



Report No.: MRI9AIKG5007727U3a Date: 2024-01-08 Page 8 of 10

# Section 12 - Ecological Information

Ecological Toxicity: No data available.

Persistence and degradability: No data available. Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

Other adverse effects: No data available.

# Section 13 - Disposal Considerations

Disposal methods:

Recommendation:

Consult state, local or national regulations to ensure proper disposal.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

# Section 14 - Transport Information

UN or ID Number	
IATA	UN3481
IMDG	UN3481
Proper Shipping Name/Description	
IATA	Lithium ion batteries contained in equipment
IMDG	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT
Packing Group	
IATA	N/A
IMDG	N/A
Hazard Label	
IATA	N/A
IMDG	N/A
Environmental hazards	
Marine pollutant:	No
IMDG EmS:	F-A. S-I
Special precautions for user	No information available.

Transport information: The Rechargeable Li-ion Battery 401029 has passed the test UN38.3, according to the report ID: MRI9AIKG5007627U5.

PONY-BGLS186-03E-027-2023B



Report No.: MRI9AIKG5007727U3a Date: 2024-01-08 Page 9 of 10

According to the Packing Instruction 967 section II of IATA DGR 65<sup>th</sup> Edition for transportation.

According to the special provision 188 of IMDG (41-22), the goods are not subject to other provision of this code.

Note: Batteries weight in the package < 5kg. (By air, Batteries installed in equipment)

Transport Fashion: By air, by sea.

# Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

CAS No.	TSCA	IECSC	DSL/NDSL	EINECS/ ELINCS/ NLP
12190-79-3	Listed	Listed	Listed DSL	Listed
1333-86-4	Listed	Listed	Listed DSL	Listed
24937-79-9	Listed	Listed	Listed DSL	Listed
7429-90-5	Listed	Listed	Listed DSL	Listed
7782-42-5	Listed	Listed	Listed DSL	Listed
9003-55-8	Listed	Listed	Listed DSL	Listed
9004-32-4	Listed	Listed	Listed DSL	Listed
7440-50-8	Listed	Listed	Listed DSL	Listed
7440-02-0	Listed	Listed	Listed DSL	Listed
21324-40-3	Listed	Listed	Listed DSL	Listed
9002-88-4	Listed	Listed	Listed DSL	Listed
24937-16-4	Listed	Listed	Listed DSL	Listed
9003-07-0	Listed	Listed	Listed DSL	Listed

### Section 16 - Other Information

Issue Date: 2024-01-08

Issue Department: Technical department

Modification record: Notice to reader

( Hotline 400-819-5688 Pony Testing Group Shenzhen Co., Ltd. www.ponytest.com



Report No.: MRI9AIKG5007727U3a Date: 2024-01-08 Page 10 of 10

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Other Information:

CAS: (Chemical Abstracts Service);

EC: (European Commission);

ACGIH: (American Conference of Governmental Industrial Hygienists);

NIOSH: (US National Institute for Occupational Safety and Health);

OSHA: (US Occupational Safety and Health);

TLV: (Threshold Limit Value)

TWA: (Time Weighted Average);

STEL: (Short Term Exposure Limit);

PEL: (Permissible Exposure Level);

REL: (Recommended Exposure Limit);

PC-STEL: (Permissible concentration-short time exposure limit);

PC-TWA: (Permissible concentration-time weighted average);

IARC: (International Agency for Research on Cancer);

LC50: (Lethal concentration, 50 percent kill);

LD50: (Lethal dose, 50 percent kill);

EC50: (Median effective concentration);

BCF: (Bioconcentration Factor);

BOD: (Biochemical oxygen demand);

IECSC: (Inventory of Existing Chemical Substances in China);

NOEC: (No observed effect concentration);

NTP: (US National Toxicology Program);

RTECS: (Registry of Toxic Effects of Chemical Substances);

TOC: (Total Organic Carbon);

TSCA: (Toxic Substances Control Act of USA);

DSL: (the Domestic Substances List of Canada);

NDSL: (the Non-domestic Substances List of Canada);

IATA: (International Air Transport Association);


IMDG: (International Maritime Dangerous Goods);

TDG: (Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations)

The original report which report No. is MRI9AIKG5007727U3 be replaced by this report, and it will be canceled immediately and doesn't have any legal validity. Please compliance with this report. 2024-01-08

Chunmei Zheng Approver:

\*\*\*End of report\*\*\*



PONY-BGLS186-03E-027-2023B

Address: 3/F. of Building 2, Building 1, Xinhaosheng Industrial Park, Yonghe Road, Qiaotou Community, Baoan District, Shenzhen, Guangdong, China Testing Address: 3/F. of Building 2, Building 1, Xinhaosheng Industrial Park, Yonghe Road, Qiaotou Community, Baoan District, Shenzhen, Guangdong, China Tel: 0755-26050909



